


Kuggremskivor i bussningsutförande för kuggremmar med HTD-profil


Delning 8 mm

8 M 20


Beteckning	Tandantal	Ulf	D _o mm	D _y mm	D _f mm	D _i mm	W mm	H mm	Z mm	Y mm	Bussning	Max axelhål	Vikt kg
BL 22 8 M 20	22	4	56.02	54.65	60	37	28	-	6	22	1008	25	0.29
BL 24 8 M 20	24	4	61.12	59.74	66	44	28	-	6	22	1108	28	0.32
BL 26 8 M 20	26	4	66.21	64.84	70	45	28	-	6	22	1108	28	0.36
BL 28 8 M 20	28	4	71.30	69.93	75	50	28	-	6	22	1108	28	0.44
BL 30 8 M 20	30	4	76.39	75.02	83	58	28	-	6	22	1108	28	0.55
BL 32 8 M 20	32	4	81.49	80.12	87	63	28	-	3	25	1610	42	0.65
BL 34 8 M 20	34	4	86.58	85.21	91	64	28	-	3	25	1610	42	0.70
BL 36 8 M 20	36	4	91.67	90.30	97	68	28	-	3	25	1610	42	0.78
BL 38 8 M 20	38	4	96.77	95.39	102	72	28	-	3	25	1610	42	0.87
BL 40 8 M 20	40	4	101.86	100.49	106	76	28	-	3	25	1610	42	1.02
BL 44 8 M 20	44	1	112.05	110.67	120	-	28	92	4	32	2012	50	1.23
BL 48 8 M 20	48	1	122.23	120.86	128	-	28	96	4	32	2012	50	1.57
BL 56 8 M 20	56	1	142.60	141.23	150	-	28	110	4	32	2012	50	2.20
BL 64 8 M 20	64	6	162.97	161.60	168	137	28	110	4	32	2012	50	2.69
BL 72 8 M 20	72	6	183.35	181.97	192	158	28	110	4	32	2012	50	3.16
BL 80 8 M 20	80	9	203.72	202.35	-	180	28	110	4	32	2012	50	4.50
BL 90 8 M 20	90	9	229.18	227.81	-	204	28	110	4	32	2012	50	6.30




1




2



4



5



6

8 M 30

Beteckning	Tandantal	Ulf	D _o mm	D _y mm	D _f mm	D _i mm	W mm	H mm	Z mm	Y mm	Bussning	Max axelhål	Vikt kg
BL 22 8 M 30	22	4	56.02	54.65	60	37	38	-	16	22	1008	25	0.36
BL 24 8 M 30	24	4	61.12	59.74	66	44	38	-	16	22	1108	28	0.40
BL 26 8 M 30	26	4	66.21	64.84	70	44	38	-	16	22	1108	28	0.44
BL 28 8 M 30	28	4	71.30	69.93	75	50	38	-	13	25	1210	32	0.54
BL 30 8 M 30	30	8	76.39	75.02	83	-	38	-	-	38	1615	42	0.66
BL 32 8 M 30	32	8	81.49	80.12	87	-	38	-	-	38	1615	42	0.76
BL 34 8 M 30	34	8	86.58	85.21	91	-	38	-	-	38	1615	42	0.80
BL 36 8 M 30	36	8	91.67	90.30	97	-	38	-	-	38	1615	42	0.98
BL 38 8 M 30	38	8	96.77	95.39	102	-	38	-	-	38	1615	42	1.04
BL 40 8 M 30	40	8	101.86	100.49	106	-	38	-	-	38	1615	42	1.20
BL 44 8 M 30	44	4	112.05	110.67	120	86	38	-	6	32	2012	50	1.38
BL 48 8 M 30	48	4	122.23	120.86	128	90	38	-	6	32	2012	50	1.83
BL 56 8 M 30	56	4	142.60	141.23	150	110	38	-	6	32	2012	50	2.75
BL 64 8 M 30	64	1	162.97	161.60	168	-	38	115	7	45	2517	65	4.50
BL 72 8 M 30	72	6	183.35	181.97	192	158	38	120	7	45	2517	65	6.00
BL 80 8 M 30	80	9	203.72	202.35	-	180	38	120	7	45	2517	65	6.10
BL 90 8 M 30	90	9	229.18	227.81	-	204	38	120	7	45	2517	65	6.20
BL 112 8 M 30	112	9	285.21	283.83	-	254	38	120	7	45	2517	65	7.90
BL 144 8 M 30	144	12	366.69	365.32	-	336	38	120	7	45	2517	65	9.80


8 M 50

Beteckning	Tandantal	Ulf	D _o mm	D _y mm	D _f mm	D _i mm	W mm	H mm	Z mm	Y mm	Bussning	Max axelhål	Vikt kg
BL 28 8 M 50	28	4	71.30	69.93	75	50	60	-	19	22	1108	28	0.76
BL 30 8 M 50	30	4	76.39	75.02	83	58	60	-	22	38	1615	42	0.95
BL 32 8 M 50	32	4	81.49	80.12	87	63	60	-	22	38	1615	42	0.98
BL 34 8 M 50	34	4	86.58	85.21	91	65	60	-	22	38	1615	42	1.00
BL 36 8 M 50	36	4	91.67	90.30	97	68	60	-	22	38	1615	42	1.20
BL 38 8 M 50	38	4	96.77	95.39	102	72	60	-	22	38	1615	42	1.43
BL 40 8 M 50	40	2	101.86	100.49	106	80	60	-	14	32	2012	50	1.65
BL 44 8 M 50	44	2	112.05	110.67	120	86	60	-	14	32	2012	50	1.80
BL 48 8 M 50	48	2	122.23	120.86	128	95	60	-	14	32	2012	50	2.41
BL 56 8 M 50	56	2	142.60	141.23	150	116	60	-	7.5	45	2517	65	3.80
BL 64 8 M 50	64	2	162.97	161.60	168	136	60	-	7.5	45	2517	65	5.00
BL 72 8 M 50	72	5	183.35	181.97	192	158	60	115	7.5	45	2517	65	6.70
BL 80 8 M 50	80	2	203.72	202.35	-	180	60	140	4.5	51	3020	75	7.50
BL 90 8 M 50	90	5	229.18	227.81	-	204	60	146	4.5	51	3020	75	8.00
BL 112 8 M 50	112	5	285.21	283.83	-	254	60	146	4.5	51	3020	75	9.50
BL 144 8 M 50	144	14	366.69	365.32	-	336	60	146	4.5	51	3020	75	12.80
BL 168 8 M 50	168	12	427.80	426.42	-	395	60	146	4.5	51	3020	75	17.50
BL 192 8 M 50	192	12	488.92	487.54	-	455	60	146	4.5	51	3020	75	20.00


Material: Z ≤ 72 stål
Z ≥ 80 gjutjärn

8 M 85


Beteckning	Tand- antal	Utf	D _o mm	D _y mm	D _f mm	D _i mm	W mm	H mm	Z mm	Y mm	Bussning	Max axelhål	Vikt kg
BL 34 8 M 85	34	2	86.58	85.21	91	65	95	-	28.5	38	1615	42	1.20
BL 36 8 M 85	36	2	91.67	90.30	97	68	95	-	28.5	38	1615	42	1.60
BL 38 8 M 85	38	2	96.77	95.39	102	72	95	-	28.5	38	1615	42	2.05
BL 40 8 M 85	40	2	101.86	100.49	106	80	95	-	31.5	32	2012	50	2.25
BL 44 8 M 85	44	2	112.05	110.67	120	86	95	-	31.5	32	2012	50	2.55
BL 48 8 M 85	48	2	122.23	120.86	128	97	95	-	25	45	2517	65	3.20
BL 56 8 M 85	56	2	142.60	141.23	150	116	95	-	25	45	2517	65	3.72
BL 64 8 M 85	64	2	162.97	161.60	168	136	95	-	25	45	2517	65	6.00
BL 72 8 M 85	72	2	183.35	181.97	192	150	95	-	22	51	3020	75	7.20
BL 80 8 M 85	80	7	203.72	202.35	-	180	95	-	22	51	3020	75	8.80
BL 90 8 M 85	90	7	229.18	227.81	-	204	95	-	22	51	3020	75	10.00
BL 112 8 M 85	112	7	285.21	283.83	-	254	95	170	22	51	3020	75	12.40
BL 144 8 M 85	144	7	356.69	365.32	-	336	95	198	15	65	3525	100	18.50
BL 168 8 M 85	168	14	427.80	426.42	-	395	95	198	15	65	3525	100	21.30
BL 192 8 M 85	192	14	488.92	487.54	-	455	95	198	15	65	3525	100	27.20




7




8



9



12



14

Delning 14 mm

Material: Z ≤ 72 stål
Z ≥ 80 gjutjärn

14 M 40

Beteckning	Tand- antal	Utf	D _o mm	D _y mm	D _f mm	D _i mm	W mm	H mm	Z mm	Y mm	Bussning	Max axelhål	Vikt kg
BL 28 14 M 40	28	2	124.78	121.98	128	94	54	-	11	32	2012	50	2.30
BL 29 14 M 40	29	2	129.23	126.44	138	98	54	-	11	32	2012	50	2.70
BL 30 14 M 40	30	2	133.69	130.90	138	98	54	-	11	32	2012	50	3.00
BL 32 14 M 40	32	2	142.60	139.81	154	108	54	-	11	32	2012	50	3.40
BL 34 14 M 40	34	2	151.52	148.72	160	110	54	-	4.5	45	2517	65	3.60
BL 36 14 M 40	36	2	160.43	157.63	168	120	54	-	4.5	45	2517	65	4.25
BL 38 14 M 40	38	2	169.34	166.55	183	130	54	-	4.5	45	2517	65	4.90
BL 40 14 M 40	40	2	178.25	175.46	188	138	54	-	4.5	45	2517	65	5.70
BL 44 14 M 40	44	2	196.08	193.28	211	155	54	-	1.5	51	3020	75	7.00
BL 48 14 M 40	48	2	213.90	211.11	226	170	54	-	1.5	51	3020	75	8.00
BL 56 14 M 40	56	2	249.56	246.76	256	208	54	-	1.5	51	3020	75	9.60
BL 64 14 M 40	64	5	285.21	282.41	296	240	54	170	1.5	51	3020	75	12.30
BL 72 14 M 40	72	14	320.86	318.06	-	280	54	170	1.5	51	3020	75	16.00
BL 80 14 M 40	80	7	356.51	353.71	-	315	54	170	1.5	51	3020	75	16.10
BL 90 14 M 40	90	7	401.07	398.28	-	360	54	170	1.5	51	3020	75	16.30
BL 112 14 M40	112	7	499.11	496.32	-	457	54	170	1.5	51	3020	75	24.00
BL 144 14 M40	144	7	641.71	638.92	-	600	54	170	1.5	51	3020	75	31.70
BL 168 14M40	168	7	748.66	745.87	-	706	54	170	1.5	51	3020	75	44.00
BL 192 14M40	192	7	855.62	852.82	-	813	54	170	1.5	51	3020	75	49.00
*BL 216 14M40	216	7	962.57	959.76	-	920	54	170	1.5	51	3020	75	55.00

*Tillverkas på förfrågan

14 M 55


Beteckning	Tand- antal	Utf	D _o mm	D _y mm	D _f mm	D _i mm	W mm	H mm	Z mm	Y mm	Bussning	Max axelhål	Vikt kg
BL 28 14 M 55	28	2	124.78	121.98	128	94	70	-	19	32	2012	50	2.72
BL 29 14 M 55	29	2	129.23	126.44	138	100	70	-	19	32	2012	50	2.90
BL 30 14 M 55	30	2	133.69	130.90	138	100	70	-	12.5	45	2517	65	3.30
BL 32 14 M 55	32	2	142.60	139.81	154	108	70	-	12.5	45	2517	65	3.50
BL 34 14 M 55	34	2	151.52	148.72	160	110	70	-	12.5	45	2517	65	4.20
BL 36 14 M 55	36	2	160.43	157.63	168	120	70	-	12.5	45	2517	65	4.68
BL 38 14 M 55	38	2	169.34	166.55	183	130	70	-	12.5	45	2517	65	5.60
BL 40 14 M 55	40	2	178.25	175.46	188	138	70	-	12.5	45	2517	65	6.00
BL 44 14 M 55	44	2	196.08	193.28	211	155	70	-	9.5	51	3020	75	8.00
BL 48 14 M 55	48	2	213.90	211.11	226	170	70	146	9.5	51	3020	75	10.00
BL 56 14 M 55	56	2	249.56	246.76	256	208	70	146	9.5	51	3020	75	11.40
BL 64 14 M 55	64	5	285.21	282.41	296	240	70	146	9.5	51	3020	75	13.90
BL 72 14 M 55	72	14	320.86	318.06	-	280	70	146	9.5	51	3020	75	15.30
BL 80 14 M 55	80	7	356.51	353.71	-	315	70	146	9.5	51	3020	75	16.50
BL 90 14 M 55	90	7	401.07	398.28	-	360	70	146	9.5	51	3020	75	19.00
BL 112 14 M55	112	7	499.11	496.32	-	457	70	146	9.5	51	3020	75	27.50
BL 144 14 M55	144	7	641.71	638.92	-	600	70	146	9.5	51	3020	75	35.50
BL 168 14M55	168	7	748.66	745.87	-	706	70	146	9.5	51	3020	75	49.00
BL 192 14M55	192	7	855.62	852.82	-	813	70	178	19	89	3535	90	53.00
*BL 216 14M55	216	7	962.57	959.76	-	920	70	178	19	89	3535	90	65.80

*Tillverkas på förfrågan


Material: Z ≤ 48 stål
Z ≥ 56 gjutjärn

14 M 85


Beteckning	Tand- antal	Uff	D _o mm	D _y mm	D _f mm	D _i mm	W mm	H mm	Z mm	Y mm	Bussning	Max axelhål	Vikt kg
BL 28 14 M 85	28	2	124.78	121.98	128	98	102	-	28.5	45	2517	65	3.00
BL 29 14 M 85	29	2	129.23	126.44	138	100	102	-	28.5	45	2517	65	3.50
BL 30 14 M 85	30	2	133.69	130.90	138	100	102	-	28.5	45	2517	65	3.90
BL 32 14 M 85	32	2	142.60	139.81	154	108	102	-	28.5	45	2517	65	4.20
BL 34 14 M 85	34	2	151.52	148.72	160	110	102	-	28.5	45	2517	65	5.50
BL 36 14 M 85	36	2	160.43	157.63	168	125	102	-	25.5	51	3020	75	6.80
BL 38 14 M 85	38	2	169.34	166.55	183	130	102	-	25.5	51	3020	75	8.00
BL 40 14 M 85	40	2	178.25	175.46	188	138	102	-	25.5	51	3020	75	10.00
BL 44 14 M 85	44	2	196.08	193.28	211	153	102	-	25.5	76	3030	75	11.00
BL 48 14 M 85	48	2	213.90	211.11	226	171	102	-	25.5	76	3030	75	13.70
BL 56 14 M 85	56	2	249.56	246.76	256	210	102	-	18.5	65	3525	100	21.60
BL 64 14 M 85	64	5	285.21	282.41	296	240	102	190	18.5	65	3525	100	28.80
BL 72 14 M 85	72	14	320.86	318.06	-	280	102	190	18.5	65	3525	100	26.00
BL 80 14 M 85	80	7	356.51	353.71	-	315	102	190	18.5	65	3525	100	29.00
BL 90 14 M 85	90	7	401.07	398.28	-	360	102	190	18.5	65	3525	100	31.80
BL 112 14 M85	112	7	499.11	496.32	-	457	102	190	18.5	65	3525	100	36.50
BL 144 14 M85	144	7	641.71	638.92	-	600	102	190	18.5	65	3525	100	48.00
BL 168 14M85	168	7	748.66	745.87	-	706	102	190	18.5	65	3525	100	60.00
BL 192 14M85	192	7	855.62	852.82	-	813	102	230	-	102	4040	100	86.00
BL 216 14M85	216	7	962.57	959.76	-	920	102	230	-	102	4040	100	91.50




2



5



7



14

14 M 115

Beteckning	Tand- antal	Uff	D _o mm	D _y mm	D _f mm	D _i mm	W mm	H mm	Z mm	Y mm	Bussning	Max axelhål	Vikt kg
BL 28 14 M115	28	2	124.78	121.98	128	98	133	-	44	45	2517	65	3.60
BL 29 14 M115	29	2	129.23	126.44	138	100	133	-	44	45	2517	65	4.20
BL 30 14 M115	30	2	133.69	130.90	138	100	133	-	44	45	2517	65	4.60
BL 32 14 M115	32	2	142.60	139.81	154	108	133	-	44	45	2517	65	5.00
BL 34 14 M115	34	2	151.52	148.72	160	110	133	-	44	45	2517	65	6.50
BL 36 14 M115	36	2	160.43	157.63	168	125	133	-	41	51	3020	75	8.00
BL 38 14 M115	38	2	169.34	166.55	183	130	133	-	41	51	3020	75	9.20
BL 40 14 M115	40	2	178.25	175.46	188	138	133	-	41	51	3020	75	9.50
BL 44 14 M115	44	2	196.08	193.28	211	155	133	-	28.5	76	3030	75	13.00
BL 48 14 M115	48	2	213.90	211.11	226	170	133	-	28.5	76	3030	75	15.80
BL 56 14 M115	56	2	249.56	246.76	256	210	133	-	22	89	3535	90	24.00
BL 64 14 M115	64	5	285.21	282.41	296	240	133	190	22	89	3535	90	29.00
BL 72 14 M115	72	14	320.86	318.06	-	280	133	190	22	89	3535	90	31.00
BL 80 14 M115	80	7	356.51	353.71	-	315	133	190	22	89	3535	90	33.10
BL 90 14 M115	90	7	401.07	398.28	-	360	133	190	22	89	3535	90	37.00
BL 112 14M115	112	7	499.11	496.32	-	457	133	190	22	89	3535	90	49.00
BL 144 14M115	144	7	641.71	638.92	-	600	133	230	15.5	102	4040	100	63.00
BL 168 14M115	168	7	748.66	745.87	-	706	133	230	15.5	102	4040	100	82.60
BL 192 14M115	192	7	855.62	852.82	-	813	133	230	15.5	102	4040	100	96.00
*BL 216 14M115	216	7	962.57	959.76	-	920	133	230	15.5	102	4040	100	107.00

*Tillverkas på förfrågan

14 M 170

Beteckning	Tand- antal	Uff	D _o mm	D _y mm	D _f mm	D _i mm	W mm	H mm	Z mm	Y mm	Bussning	Max axelhål	Vikt kg
BL 38 14 M170	38	2	169.34	166.55	183	130	187	-	55.5	76	3030	75	12.00
BL 40 14 M170	40	2	178.25	175.46	188	138	187	-	55.5	76	3030	75	12.40
BL 44 14 M170	44	2	196.08	193.28	211	155	187	-	49	89	3535	90	17.00
BL 48 14 M170	48	2	213.90	211.11	226	175	187	-	49	89	3535	90	19.00
BL 56 14 M170	56	2	249.56	246.76	256	210	187	-	49	89	3535	90	21.60
BL 64 14 M170	64	2	285.21	282.41	296	240	187	-	42.5	102	4040	100	39.00
BL 72 14 M170	72	14	320.86	318.06	-	280	187	230	42.5	102	4040	100	41.20
BL 80 14 M170	80	14	356.51	353.71	-	315	187	230	42.5	102	4040	100	44.80
BL 90 14 M170	90	7	401.07	398.28	-	360	187	230	42.5	102	4040	100	47.00
BL 112 14 M170	112	7	499.11	496.32	-	457	187	265	30	127	5050	125	68.60
BL 144 14 M170	144	7	641.71	638.92	-	600	187	265	30	127	5050	125	86.00
BL 168 14M170	168	7	748.66	745.87	-	706	187	265	30	127	5050	125	116.00
*BL 192 14M170	192	7	855.62	852.82	-	813	187	265	30	127	5050	125	134.00
*BL 216 14M170	216	7	962.57	959.76	-	920	187	265	30	127	5050	125	146.50

*Tillverkas på förfrågan

Material: Z ≤ 48 stål
Z ≥ 56 gjutjärn